

# Package: bolder (via r-universe)

June 2, 2026

**Title** 'RStudio' Add-Ins for Formatted Section Titles

**Version** 0.1.1

**Description** Provides 'RStudio' add-ins and helper functions for converting the current editor line, or a supplied character string, into formatted section titles for 'R' scripts. When used as an add-in, it uses 'rstudioapi' to read the active document context and replace only the selected line, so users can bind the add-ins to keyboard shortcuts. The formatter trims common comment and heading markers, converts the label to uppercase, and renders three styles: a five-line boxed title, a framed subtitle, and a simple inline header. Generated titles are padded or centered to a configurable width, using the package-specific width option when set and the session display width otherwise, which helps keep analysis scripts visually consistent and easier to navigate.

**License** MIT + file LICENSE

**Encoding** UTF-8

**Imports** rstudioapi

**NeedsCompilation** no

**Repository** <https://freitascurti.r-universe.dev>

**Date/Publication** 2026-06-01 17:04:59 UTC

**RemoteUrl** <https://github.com/freitascurti/bolder>

**RemoteRef** HEAD

**RemoteSha** f7250edc75936dc3fd7f4c6f8254458d7a89e936

## Contents

bolder_format_title . . . . .	2
bolder_simple . . . . .	3
bolder_subtitle . . . . .	3
bolder_title . . . . .	3

<b>Index</b>	<b>4</b>
--------------	----------

---

`bolder_format_title`    *Format a bolder title*

---

## **Description**

Formats text using the bolder title styles.

## **Usage**

```
bolder_format_title(  
    text,  
    level = c("title", "subtitle", "simple"),  
    width = bolder_width()  
)
```

## **Arguments**

<code>text</code>	Text to format as a title.
<code>level</code>	Title level: title, subtitle, or simple.
<code>width</code>	Total title width. Defaults to <code>getOption("bolder.width")</code> when set, otherwise <code>getOption("width")</code> .

## **Details**

Set options(`bolder.width = 90`) to customize the generated title width for addins and direct calls that use the default width argument.

## **Value**

A character string containing the formatted title.

## **Examples**

```
bolder_format_title("base de dados", "title")  
bolder_format_title("base de dados", "subtitle")  
bolder_format_title("base de dados", "simple")
```

---

bolder_simple	<i>Create a simple bolder title</i>
---------------	-------------------------------------

---

**Description**

RStudio addin that replaces the current editor line with a simple inline bolder title.

**Usage**

```
bolder_simple()
```

**Value**

Invisibly returns the generated replacement string. Called for the side effect of replacing the current editor line in RStudio.

---

bolder_subtitle	<i>Create a bolder subtitle</i>
-----------------	---------------------------------

---

**Description**

RStudio addin that replaces the current editor line with a centered bolder subtitle.

**Usage**

```
bolder_subtitle()
```

**Value**

Invisibly returns the generated replacement string. Called for the side effect of replacing the current editor line in RStudio.

---

bolder_title	<i>Create a bolder title</i>
--------------	------------------------------

---

**Description**

RStudio addin that replaces the current editor line with a centered bolder title.

**Usage**

```
bolder_title()
```

**Value**

Invisibly returns the generated replacement string. Called for the side effect of replacing the current editor line in RStudio.

# Index

`bolder_format_title`, 2  
`bolder_simple`, 3  
`bolder_subtitle`, 3  
`bolder_title`, 3